Phone: 888-505-0390 Fax: 574-546-2466

www.pslubricants.com

PO Box 389 809 Douglas Street Bremen, IN 46506

Product Information

15W40 ALTRA FLEET MOTOR OIL

Altra Fleet Motor Oil is a heavy duty engine oil that is formulated from universal fluids to meet or exceed the warranty requirements of most mafor manufacturers of desiel and gasoline engines. They meet certain requirements of Detriot Desiel, Cummins, Mack, Caterpillar, and Allison, and are API certified under the EOLCS system, license number 2047.

Altra Fleet Motor Oil can be used with complete success in most desiel as well as exhaust gas recirculated engines used in truck or off-highway equipment. They may also be used for manual transmission ans hyrdaulic systems where motor oil is recommended.

Always consult owners manual for proper viscosity and performance recommendattions.

	SAE
SPECIFICATIONS	15W-40
API Gravity	29.3
cSt @ 40° C	119.7
cSt @ 100°C	15.5
SUS @ 100° F	556
SUS @ 210° F	80
VIS. Index	136
Pour Point, °F	-20
Sulfated Ash, % wt.	.90
TBN (ASTM D-2896)	8.3

USER BENEFITS

- Reduced engine wear
- Increased engine cleanliness
- Performance tested
- Select paraffin base oils
- Highest natural viscosity index
- Lubricity and resistance to water & oxidation
- Special additives for longer oil life
- Extended oil drains
- Greatly reduced oil consumption
- API CJ-4, CI-4, CI-4 Plus, SM

PERFORMANCE STANDARDS

Has successfully completed the testing requirements for: API service classifications; CJ-4, CI-4, CI-4 Plus, SM, SL, Sj and SH. Mack EO-O Premium Plus, Eo-M Plus, EO-N Plus. Detroit Diesel, CI-4 Plus, Caterpillar ECF-1, ECF-2, and ECF-3. Allison C-3, Cummins CES 20081 John Deere, International Harvester and Ford specification.

CONTAINER SIZES

275 - Galon Totes 55 - Gallon Drums