Phone: 888-505-0390 Fax: 574-546-2466 www.pslubricants.com PO Box 389 809 Douglas Street Bremen, IN 46506

Red

515

- 5

NO. 400 SPECIAL HEAVY-DUTY TRANSMISSION OIL SAE 50

DESCRIPTION

P. S. Special Heavy-Duty Transmission Oil is a **SAE 50** oil in viscosity. This oil is blended with a unique heavy-duty engine oil additive package that has been modified to meet the requirements for **MT-1** (manual transmissions) with a **GL-1** additive level.

This **special** transmission oil is thermally stable and will not varnish at elevated temperatures. This oil also contains rust and oxidation inhibitors and contains a heavy-duty anti-wear/friction modifier to keep wear to a minimum.

This oil should not be construed as an **E. P.** oil and should not be used in applications where an **E. P.** oil is required such as in wheel bearings, power dividers and differentials where a GL-4/GL-5 is required.

CONTAINER SIZES

5 Gallon Pail 16 Gallon Keg 55 Gallon Drums

TYPICAL SPECIFICATIONS SAE GRADE 50 Gravity, °API 28 Vis., SUS @ 100°F. 900 Vis., SUS @ 210°F. 85 Viscosity Index, min. 95

USER BENEFITS

- ★ High temperature stability
- * Rust and oxidation stability
- ★ Anti-wear/friction modifier
- ★ Exceptionally long life oil
- ★ Longer oil drains
- ★ Longer seal life

Color

Flash Point, °F.

Pour Point, °F.

★ Extended parts life