



# PETROLEUM SOLUTIONS

Specializing in Quality Lubricants and Fuel Additives

Phone: 888-505-0390  
 Fax: 574-546-2466  
[www.pslubricants.com](http://www.pslubricants.com)

PO Box 389  
 809 Douglas Street  
 Bremen, IN 46506

## Product Information

### NO. 4022

### CENTRAL LUBRICATION SYSTEM GREASE

#### DESCRIPTION

No. 4022 C.L.S. was formulated specifically for Centralized Lubrication Systems. This lubricant has excellent pumpability characteristics and will not harden under pressure. Contains the proper balance between Extreme Pressure and Anti-wear additives and carries a 60 O.K. Timken pressure load. Fortified with anti-rust and corrosion additives to resist attack by water or citric acids. Highly water resistant and has a dropping point of over 480° F. No. 4022 will stand intermittent temperatures up to 540° F and has excellent reversibility characteristics. Slightly tacky and does not work down or sling.

#### APPLICATION

Designed primarily for Central Lubrication Systems. May also be used where a lighter lubricant is desired due to pumpability or where a semi-fluid grease is required. Highly recommended for some enclosed gear cases that require a semi-fluid grease.

#### TYPICAL SPECS

	No. 4022	No. 4021	No. 4020
N.L.G.I.	1	0	00
Penetration	310	350	380
Dropping Point, ° F	540+	540+	540+
Base (Soap Type)	Calcium Sulfonate		
Timken O.K. Load	60	60	60

#### BASE OIL SPECS

SUS @ 100° F	1000
SUS @ 210° F	65
Flash Point	430
Pour Point	-10

#### CONTAINER SIZES

35 Lb. Pails  
 120 Lb. Kegs  
 400 Lb. Barrels