Phone: 888-505-0390 Fax: 574-546-2466 www.pslubricants.com PO Box 389 809 Douglas Street Bremen, IN 46506

Product Information

NO. 4048 MULTI-PURPOSE GREASE

NO. 4048 MULTI-PURPOSE GREASE

is a premium lithium complex grease. This multi - purpose lithium complex grease has a high dropping point in excess of 500 F, which insures retention where high temperatures are encountered. This product has been formulated with a special additive package which insures high film strength, extreme pressure (EP) and anti-wear properties, and is recommended for a variety of automotive, agricultural, mining, and industrial applications, including disc brake wheel bearings, universal joints, and conveyor bearings.

The high quality virgin base fluids provide excellent natural oxidation inhibition. This combined with effective antioxidants as well as corrosion inhibitors provide extra stability under storage and extreme service conditions.

PRODUCT BENEFITS

Has multi-use purposes as well as extra stability under storage and extreme service conditions.

RECOMMENDED APPLICATIONS

For use in/on any of the following:

- Heavily loaded plain and rolling-element bearings in agriculture and construction
- Mining and industrial equipment
- Wheel bearings of passenger cars, trucks, high-performance vehicles
- SUV's and motorcycles equipped with disc brakes
- Ball joints/universal joints
- Grease guns in auto repair shops
- Conveyor bearings

NO. 4048 NLGI #2 TYPICAL SPECIFICATIONS:

| NLGI | No. 2 |
|-----------------------------|----------|
| Texture | Tacky |
| Dropping Point | 500 |
| Timken Load Carring Test | 80 |
| Operating Temp. Range -10°F | to 325°F |

Meets NLGI Certification GC-LB.

Container Sizes

420#- Gallon Drums 120# - Kegs