



PRODUCT INFORMATION SHEET

NO. 4092

ULTRAPLEX GREASE NO. 2

ULTRAPLEX is an outstanding complex base grease especially formulated for moisture, high temperatures and heavy loaded conditions.

ULTRAPLEX is a fibrous, slightly tacky complex grease with superior mechanical stability and is an exceptional long life type lubricant.

ULTRAPLEX will not soften or work down under heat or pressure and is completely water resistant with the rust and corrosion inhibitors.

ULTRAPLEX performs well at elevated temperatures up to 400° F and will withstand intermittent temperatures to 450° F and has excellent reversibility characteristics.

ULTRAPLEX is compounded with the proper balance between anti-wear and extreme pressure additives to hold wear to a minimum. Select base stocks are coupled to grease base with special polymers to resist bleeding and separation to ensure a long lasting grease.

TYPICAL SPECIFICATIONS

SEPARATED MINERAL OIL:

Vis., SUS @ 100° F	900
Vis., SUS @ 210° F	87
Viscosity Index	110
Flash Point, ° F	480
Fire Point, ° F	500
Pour Point, ° F	-25
Dropping Point, ° F	540 min.

THICKENER

Lith. Comp.

INSPECTION DATA:

Penetration, D-217 10,000s	265
Oxidation, D-942-PSI Loss 500 Hrs	7
Timken, D-2509, #OK Load	50
4-Ball, D-2596 (Weld)	200 kg
(LWI)	36.4
Life Performance, D-3527	500

CONTAINER SIZES

50 Tube Case
35 Lb. Pails
120 Lb. Kegs
400 Lb. Barrels