



## Product Information

### 6500 TRACTOR POWER FLUID

#### DESCRIPTION

6500 heavy duty tractor hydraulic power fluid provides excellent extreme pressure protection for maximum gear life and capacity for wet brakes and power take off clutches, excellent wet brake noise suppression and filterability characteristics. This power fluid was designed to meet and exceed all performance requirements of manufacturers using gear-hydraulic combination systems.

This Power Fluid is able to achieve these results while meeting requirements for corrosion and rust inhibition, water tolerance, and temperature operation range. This data is supported in the form of approvals from major manufacturers and extensive field service trail experience.

6500 Power fluid is suitable for use in applications specifying the following fluids:

Massey-Ferguson CMS M114, CMS M1143, CMS M1141, CMS M1138, CMS M1135, Permatran III White Q-1826, Allison C-4, API GL-4, Case New Holland MAT3505, MAT3525, MAT3526, ESN M2C86B, Eaton Vickers 694 ATS-373 w/35VQ25, JI Case MS-1204 through MS 1206 & JI Case MS-1210, JCMASHK P-041 & JCMASHK P-042  
John Deere J-20C, Komatsu,  
Kubota UDT & Kubota Super UDT,  
Volvo VCE 1273.03 & Volvo WB101  
Steiger HydrTrans Fluid, Sauer Sunstrand,  
Danfoss HydroStatic Trans Fluid, Sperry  
Vickers/Eaton I-286S, Sperry Vickers/Eaton M2950S  
HyTran Plus and HyTran Ultra & B-6 by HyTran

#### USER BENEFITS

- Lower Operating Temperatures
- One Fluid for All Units
- Non-Foaming
- Paraffin Oil and Special Oxidation Inhibitors Give Longer Oil Life
- Reduced Downtime - Longer Equipment Life
- Excellent Extreme Pressure Qualities
- Even Power Flow
- Low Pour Point
- Reduced Fluid Consumption

#### TYPICAL SPECIFICATIONS

Viscosity @ 40° C cSt	42
Viscosity @ 100° C cSt	7.9
Gravity, API	31.1
Viscosity Index	162
Flash Point	350
Pour Point, °F	-30

#### CONTAINER SIZES

5 Gallon Pails  
55 Gallon Drums  
275 Gallon Totes