



Product Information

INDUSTRIAL AIR TOOL OILS

Heavy-duty lubricant is designed especially for rock drills, jackhammers, and heavy air tools. Selected and specially refined crudes are combined with special oiliness additives to give extra lubricity for extremely heavy-duty service. Contains extreme pressure additives to keep metal surfaces from galling and welding. Proper amount of adhesion and tackifier agents keep oil clinging to operating surfaces where moisture is encountered. The latest proven anti-wear agents help keep tools operating longer with less vibration and strain on personnel because of better lubrication. New dispersant package keeps small clearances free from varnish and sludge for clean, trouble free operation. Formulated for all air operated reservoirs in the tools themselves. Approved by all O.E.M. manufacturers of air tools.

USER BENEFITS

- ★ High film strength base oils
- ★ Outstanding lubricity and oiliness additives
- ★ Heavy-duty E.P. additives to prevent galling and welding
- ★ High load carrying tackifiers and adhesion additives
- ★ Dispersant package keeps tools internally clean
- ★ Less vibration through better lubrication

PHYSICAL CHARACTERISTICS - TYPICAL:

<u>Code</u>	<u>7010</u>	<u>7030</u>	<u>7050</u>
SAE Grade	10	30	50
Viscosity, SUS @ 100° F	165	540	900
SUS @ 210° F	44	64	85
Viscosity Index, min.	90	90	90
Flash Point, °F min.	400	475	500
Pour Point, °F max.	-20	10	+10
Color	Red	Red	Red

CONTAINER SIZES

5 Gallon Pails
 16 Gallon Kegs
 55 Gallon Drums