



INDUSTRIAL HYDRAULIC OIL

Turbine grade hydraulic oil is designed to meet all the demands of modern hydraulic systems. Carefully selected paraffin base oils with high viscosity indexes will hold viscosity changes to a minimum as operating temperatures vary. Contains unique oxidation inhibitor which cuts down carbon deposits. Excellent anti-wear agents keep wear to a minimum and help lower operating temperatures. Special rust inhibitor assures protection against rust and corrosion. Non-foaming and assures extended service under severe conditions.

PHYSICAL CHARACTERISTICS - TYPICAL

| Code | 7105 | 7110 | 7120 | 7130 | 7140 |
|-------------------------|-------------|-------------|-------------|-------------|-------------|
| SAE Grade | 5 | 10 | 20 | 30 | 40 |
| Gravity, °API | 32 | 31 | 30 | 28.5 | 27 |
| Viscosity, SUS @ 100° F | 150 | 200 | 305 | 550 | 725 |
| SUS @ 210° F | 43 | 46 | 53 | 64 | 74.6 |
| Viscosity Index, min. | 95 | 95 | 95 | 95 | 95 |
| Color | Red | Red | Red | Red | Red |
| Flash Point, °F, min. | 400 | 420 | 440 | 475 | 530 |
| Pour Point, °F, max. | -30 | -15 | -10 | -5 | 0 |

CONTAINER SIZES

5 Gallon Pails
16 Gallon Kegs
55 Gallon Barrels