



SYNTHETIC GEAR OIL

P. S. Synthetic gear oils are heavy-duty, extreme pressure, GL-5 enclosed gear lubricants. Formulated from quality synthesized base stocks, these synthetic gear oils exhibit very low channel points or pour points and high viscosity indexes. Compounded with extreme pressure additives, rust and corrosion protection.

P. S. Synthetic gear oils will provide outstanding performance levels over a broad range of conditions and applications. The quality base stocks will provide user with a broader range of temperatures and promote extended bearing, gear, seal and equipment life.

P. S. Synthetic gear oils are recommended for manual transmissions, differentials including limited slip, transfer cases and industrial enclosed gear cases. Especially formulated for heavy

loaded gears and adverse conditions. Fully approved for Eaton extended warranty or factory fill replacement and Mack requirements for synthetic lubricant requirements.

Please note that No. 4150 is a Non-E.P. Synthetic Oil formulated to meet the synthetic requirements and fully approved for **Eaton** extended warranty. For application requiring an extreme pressure additive package, refer to No. 4190 and No. 41140.

CONTAINER SIZES

35 Lb. Pails
120 Lb. Kegs
420 Lb. Barrels

TYPICAL SPECIFICATIONS

<u>Code</u>	<u>4150</u>	<u>4190</u>	<u>41140</u>
Vis., SUS @ 100° F.....	690	665	1221
Vis., SUS @ 200° F.....	92	90.1	150.6
Vis., CST 40° C.....	136.5	136.5	254.1
Viscosity Index	140	152	172
Pour Point, ° F.....	-40	-50	-25
SAE Grade.....	50	75W-90	80W-140
API Gravity.....	25	24.3	22.3
AGMA No.	4	4EP	5-6EP
Timken O.K. Load	35	50	50
	Non-E.P.	E.P.	E.P.