



PETROLEUM SOLUTIONS

Specializing in Quality Lubricants and Fuel Additives

Phone: 888-505-0390
 Fax: 574-546-2466
www.pslubricants.com

PO Box 389
 809 Douglas Street
 Bremen, IN 46506

NO. 1511W WINTERIZED J-MAX™ WITH DE-ICER

HEAVY-DUTY DIESEL ADDITIVE WITH COLD FLOW IMPROVER

- **WINTERIZED J-MAX** is a third generation multi-functional diesel fuel additive formulated for **ULTRA-LOW No. 2** distillate fuels and **BIO** blended fuels. **WINTERIZED J-MAX** vastly improves the low temperature operability of no.2 fuels, contains a Cetane improver and a NEW GENERATION heavy-duty detergent cleaner that provides outstanding injector cleanliness. **WINTERIZED J-MAX** also contains an improved fuel stabilizer, oxidation and thermal control to minimize deposits and formation of asphaltene particles which greatly extends filter life and the storage life of the fuel. Special lubricity agent restores the lubricity that is removed during refining.
- **WINTERIZED J-MAX** contains the latest cold flow improver developed strictly for **ULTRA-LOW** fuels and **BIO BLENDED** fuels which are marketed today. **WINTERIZED J-MAX** will lower the operability of the fuel 10 F to 20 F below the cloud point of the fuel.
- **WINTERIZED J-MAX** is a varied ratio WINTERIZED formulation to provide one winter product that covers the many problems encountered in wintertime operation and helps hold treatment cost to a minimum.

USER BENIFITS

- | | |
|--|---|
| <ul style="list-style-type: none"> • CONTAINS CENTANE IMPROVER • LUBRICITY AGENT restores lubricity to ULTRA-LOW FUELS • OUTSTANDING INJECTOR CLEANLINESS • IMPROVED FUEL STABILITY • EXTENDS FILTER LIFE • DE-ICER LOWERS FUEL LINE FREEZING POINT | <ul style="list-style-type: none"> • RESTORES POWER AND ENGINE PERFORMANCE • LOWERS OPERABILITY IN COLD WEATHER OPERATION • VASTLY IMPROVES FILTERABILITY OF NO. 2 FUELS • EXTENDS FUEL FILTER LIFE UP TO 5 TIMES LONGER • COMPATIBLE IN BIO BLENDED FUELS |
|--|---|

MIXTURE RATIO

1-2000	1-1500	1-1000
TEMPS ABOVE 10° F.	TEMPS BELOW 10° F.	TEMPS BELOW 0° F.
CETANE 2-3	CETANE 2-4	CETANE 3-5

CONTAINER SIZES

275 Gal. TOTES	55 Gal. DRUMS	2-2.5 Gal. CASES
----------------	---------------	------------------