



# Product Information Sheet

## NO. 1671 ANTI-GEL Concentrate W/ De-icer & Wax Dispersing Agent

- **1671 ANTI-GEL** has a mixture of Polymers in Hydrocarbons and contains a Paraffin Dispersing Agent that keeps wax crystals in suspensions. **1671 ANTI-GEL** also breaks down the wax crystals so they form into much smaller particles which vastly improves filterability for winter operation.
- **1671 ANTI-GEL** also contains lubricity/anti-wear agents to replace the sulfur that is removed during the refining process to hold pump wear to a minimum.
- **1671 ANTI-GEL** is formulated for today's ULTRA LOW fuels as well as BIO blended fuels.
- **1671 ANTI-GEL** when used as recommended will lower operability 10-20°F below the cloud point of the fuel and as a highly concentrated formulation affords a low treatment cost. **1671 ANTI-GEL** also has a **De-icer** that will lower the freezing point of fuel.

### USER BENIFITS

- LOWERS OPERABILITY 10-20°F
- COMPAPABLE TO 90/10 BLEND
- MORE POWER/ BETTER FUEL MILAGE THAN 90/10 BLEND
- CONTAINS LUBRICITY ADDITIVE TO PREVENT PUMP WEAR
- CONTAINS A WAX ANTI SETTLING AGENT
- DE-ICER LOWERS FUEL LINE FREEZING POINT

### MIXTURE RATIO

1-1500	1-1000	1-750
TEMPS ABOVE 0° F.	TEMPS BELOW 0° F.	EXTREME CONDITIONS

### CONTAINER SIZES

275 Gal. TOTES	55 Gal. DRUMS	2-2.5 Gal. CASES
----------------	---------------	------------------